

According to Regulation (EU) No 2015/830

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SHELL SILICON SPRAY Product code : CRX728, AT651I

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC24 Lubricants, greases and release products.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Polska Sp. z o. o.

Al. Jerozolimskie 146 02-305 Warszawa, Poland

Telephone : +48 22 822 5390
E-mail : msds@kemetyl.com
Website : www.kemetyl.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

PL - Telephone : +48 22 822 5390 (During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):

Poisons Information Center +354 543 22 22 (24/7)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP classification : Aerosols, category 1. Specific target organ toxicity after single exposure, category 3. Hazardous to

(1272/2008/EC) the aquatic environment — Chronic category 3.

Human health hazards : May cause drowsiness or dizziness. Exposure to high vapour concentrations may result in a

narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Physical/chemical hazards : Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a

naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures

exceeding 50 °C.

Environmental hazards : Harmful to aquatic life with long lasting effects.

Other information : Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short

period only. Ventilate well after use. Harmful to house pets.

2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms :





Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

Product name : Shell Silicon Spray Page 1/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container to an official chemical waste depot.

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms



Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

P501

Pressurised container: May burst if heated. H229 H336 May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects. H412

If medical advice is needed, have product container or label at hand. P101 P102

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition P210

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: Contains: Pentane .

2.3. Other hazards

Other information : The classification of this product is based on the non-aerosolised form of the mixture (on basis of

section 1.1.3.7. of Regulation (EC) No 1272/2008). Does not contain PBT or vPvB substances in

concentrations higher than 0,1%.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture. Information on hazardous substances:

	REACH nr.
(W/W) (%)	01 2110474601 22
	 01-2119474691 01-2119486944

: Shell Silicon Spray Product name Page 2/11 Date of issue : 2019-02-05 Replaces issue dated **INFO CARE SDS**



According to Regulation (EU) No 2015/830

Kemetyl

Isobutane	2,5 - < 10	75-28-5	200-857-2	01-2119485395-27
Pentane	2,5 - < 10	109-66-0	203-692-4	01-2119459286-30

Substance name	Hazard Class	H-phrases	Pictograms
Butane	Flam. Gas 1; Press.	H220; H280	GHS02; GHS04
	Gas		
Propane	Flam. Gas 1; Press.	H220; H280	GHS02; GHS04
	Gas		
Isobutane	Flam. Gas 1; Press.	H220; H280	GHS02; GHS04
	Gas		
Pentane	Aquatic Chronic 2; Asp.	H225; H304; H336;	GHS02; GHS07;
	Tox. 1; Flam. Liq. 2;	H411; EUH066	GHS08; GHS09
	STOT SE 3		

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries

up.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.

Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to

respiratory airways and coughing.

Skin contact : May cause dry skin.

Eye contact : May cause stinging of eyes and redness.
Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog.

Not suitable : Water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50

 $^\circ\text{C}.$ Do not expose emergency personnel to overheated aerosol containers. Water may be used to

cool container and prevent explosion of the aerosol.

Hazardous thermal

decomposition products

: Carbon monoxide may be evolved if incomplete combustion occurs.

Product name : Shell Silicon Spray Page 3/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

5.3. Advice for firefighters

Special protective equipment for fire-fighters

: Fight a fire where aerosols are involved from a protected position. Use adequate respiratory

equipment in case of insufficient ventilation.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact

with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours are

heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

Environmental precautions: Avoid release of product into sewers, surface water and/or ground water. Waste product should not

be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Collect

aerosol cans in an approved container. Do not pierce aerosols. Wash away remainder with plenty of

water and soap.

6.4. Reference to other sections

Reference to other sections: See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated

areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do

not breathe vapour. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep frost-free, in a cool (< 35°), dry and well-ventilated place. Protect from sunlight and keep away

from heat.

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Product name : Shell Silicon Spray Page 4/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Occupational exposure

limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Butane	GB	1450	1810	-	
Butane		1450	1810	1	MAC: MSDS Aeron
					Butane
Propane		1800	-		MAC: BG, PL, CH, SL,
					etc
Isobutane		1900	2400		MAC: FI, BE, CH
Pentane	GB	1800	-	-	
Pentane	EC	3000	-	-	Directive 2006/15/EG

Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
Pentane	Dermal				432 mg/kg bw/day
	Inhalation				3000 mg/m3

Derived no-effect level (DNEL) for consumers:

2 0.11 04 10 0.11 04 10 10 10 10 10 10 10 10 10 10 10 10 10						
Chemical name	Route of	DNEL, short-term		DNEL, long-term		
	exposure					
Local effect Syste		Systemic effect	Local effect	Systemic effect		
Pentane	Dermal				214 mg/kg bw/day	
	Inhalation				643 mg/m3	
	Oral				214 mg/kg bw/day	

Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
Pentane	Water	0,23 mg/l	0,23 mg/l	
	Sediment	1,2 mg/kg	1,2 mg/kg	
	Intermittent water			0,88 mg/l
	STP			3,6 mg/l
	Soil			0,55 mg/kg

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

Body protection : Use of specific protective industrial clothing is not required under normal conditions of use.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

with EN 140.

Hand protection : Under normal conditions of use specific gloves are not required.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Product name : Shell Silicon Spray Page 5/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

9.1. Information on basic physical and chemical properties

Appearance : Aerosol. Colour Colourless. Odour Characteristic. Odour threshold Not known.

Hq Not applicable. Waterfree product.

Not known.

Solubility in water Active ingredients not soluble. Propellant(s) not soluble.

Partition coefficient (n-oc-

tanol/water) Flash point

Not applicable. Not measurable.

Flammability (solid, gas) Contains > 85% flammable components and has a heat of combustion > Extremely flammable.

Not measurable.

Not measured. Not relevant for mixtures.

Pressurised container: May burst if heated.

30 kJ/q.

Auto ignition temperature Not applicable. Aerosol container explodes before reaching the auto-ignition point.

Boiling point/boiling range Not known.

Melting point/melting range: < -20 °C

Explosive properties

Explosion limits (% in air) 1,4 - 10,9

Oxidising properties Not applicable. Does not contain oxidizing substances.

Decomposition temperature: Not applicable. Aerosol explodes before reaching the decomposition temperature.

(air = 1)

Viscosity (20°C) Not known. Not measurable. Viscosity (40°C) Not known. Not measurable.

Vapour pressure (20°C) 8300 hPa

Vapour density (20°C) : > 1

Relative density (20°C) : 0,58 g/ml

Evaporation rate : Not known. Not relevant. Mixture of gases, liquids and solids.

9.2. Other information

Other information : Not relevant.

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

: Stable under normal conditions. Stability

10.3. Possibility of hazardous reactions

: No other hazardous reactions known. Reactivity

10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

10.5. Incompatible materials

Materials to avoid : Not applicable.

10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

Product name : Shell Silicon Spray Page 6/11

Date of issue : 2019-02-05 Replaces issue dated **INFO CARE SDS**



According to Regulation (EU) No 2015/830

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.

Inhalation

Acute toxicity: Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: < 1 %. ATE: > 5 mg/l. Low toxicity.

Not classified - based on available data, the classification criteria are not met. May cause damage to organs. Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data,

the classification criteria are not met.

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not classified - based on available data, the classification criteria are not met.

Mutagenicity : Not classified - based on available data, the classification criteria are not met.

Skin contact

Acute toxicity : Calculated LD50: no data mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Prolonged contact may dry out and defat the skin. Not classified - based on available data, the

classification criteria are not met.

Sensitisation : Does not contain skin sensitisers. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Eye contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not

met.

Ingestion

Acute toxicity : Aerosol or mist: Ingestion is unlikely to occur. Calculated LD50: > 298 mg/kg.bw. Ingredients of

unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available

data, the classification criteria are not met.

Aspiration : Contains a substance/substances with an aspiration hazard. Not classified - based on available

data, the classification criteria are not met.

Corrosion/irritation : Aerosol or mist: Ingestion is unlikely to occur. May cause a feeling of sickness, vomiting and

diarrhoea.

Carcinogenicity : Aerosol or mist: Ingestion is unlikely to occur. Does not contain carcinogenic substances. Not

classified - based on available data, the classification criteria are not met.

Mutagenicity : Aerosol or mist: Ingestion is unlikely to occur. Does not contain mutagenic substances. Not

classified - based on available data, the classification criteria are not met.

Reprotoxicity : Aerosol or mist: Ingestion is unlikely to occur. Development: Not expected to be reprotoxic.

Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the

classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
Pentane	Skin irritation	Mildly irritant	OECD 404	Rabbit
	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig
	NOAEL (development,	1000 mg/kg bw/d	OECD 414	Rat
	oral)			
	LC50 (inhalation)	> 20000 mg/m3		Rat

Product name : Shell Silicon Spray Page 7/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

Eye irritat	tion Slightly irri	itant	Rabbit
Mutageni	city Negative	OECD 47	1 Salmonella typhimurium
LD50 (ora	al) > 2000 mg	g/kg bw	Rat
NOAEL (i	inhalation) > 20000 m	ng/m3 OECD 41	Rat
NOAEL (1	fertility, inh.) 24080 mg	/m3	Rat
Skin irrita	ition Non-irritan	nt	Human

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Harmful to aquatic organisms. Calculated LC50 (fish): 68 mg/l. Calculated EC50 (waterflea): 43 mg/

I. Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence - degradability: May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility : Not applicable.

12.5. Results of PBT and vPvB assessment

PBT/vPvB assessment : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

12.6. Other adverse effects

Other information : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
	Ultimate aerobic biodegradation (%)	87 %	OECD 301 F	
	IC50 (algea)	10,7 mg/l		Selenastrum capricornutum
	EC50 (waterflea)	2,7 mg/l		Daphnia magna
	LC50 (fish)	4,26 mg/l	OECD 203	Oncorhynchus mykiss
Pentane	Log P(ow)	3,45		
Pentane	BCF	171		

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack

with waste produced by households. Containers may be recycled. Treat product residues and non-

empty pack as hazardous waste.

Additional warning : Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

Waste water discharge : Do not dispose into the environment, in drains or in water courses.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Product name : Shell Silicon Spray Page 8/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Local legislation

: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number

UN nr. : UN 1950

14.2. UN proper shipping name

Transport name : AEROSOLS Transport name (IMDG, : AEROSOLS

IATA)

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : 2
Classification code : 5F
Packaging group : Danger label : 2,1
Tunnel restriction : D

code

2

Other information : Not intended for carriage by tank-vessels on inland waterways.

IMDG (sea)

Class : 2,1 Packaging group : -

EmS (fire / spill) : F - D / S - U

Marine pollutant : No

IATA (air)

Class : 2,1

14.6. Special precautions for user

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies to

the transport of this product.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2015/830 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC

(aerosols) and other regulations.

Product name : Shell Silicon Spray Page 9/11
Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

15.2. Chemical safety assessment

Chemical safety : Not applicable.

assessment

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2015/830 dated 28 May 2015 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association IBC code : International Bulk Chemical Code

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MAC : Maximum Allowable Concentration

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development

PBT : Persistent, Bioaccumulative and Toxic

PC : Chemical product category

PT : Product type

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

SU : Sector of Use

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Flam. Aer. 1 : Expert judgement.
STOT SE 3 : Calculation method.
Aquatic Chronic 3 : Calculation method.

Full text of hazard classes mentioned in section 3:

Flam. Gas 1 : Flammable gas, category 1.
Flam. Liq. 2 : Flammable liquid, category 2.
Press. Gas : Gases under pressure.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

Asp. Tox. 1 : Aspiration hazard, category 1.

Product name : Shell Silicon Spray Page 10/11
Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Aquatic Chronic 2 : Hazardous to the aquatic environment — Chronic category 2.

Full text of H-phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

: "," used as decimal separator.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

End of safety data sheet.

Number format

Print date : 2021-06-18

Product name : Shell Silicon Spray Page 11/11

Date of issue : 2019-02-05 Replaces issue dated : --- INFO CARE SDS