

According to Regulation (EU) No 2020/878

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SHELL RUST REMOVER

Product code : CRX730, AT650I

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC24 Lubricants, greases, release agents.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Polska Sp. z o. o.

Al. Jerozolimskie 146 02-305 Warszawa, Poland

Telephone : +48 22 822 5390
E-mail : msds@kemetyl.com
Website : www.kemetyl.pl

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

PL - Telephone : +48 22 822 5390 (During office hours only)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP classification : Aerosols, category 1. Skin irritation, category 2. Specific target organ toxicity after single exposure,

(1272/2008/EC) category 3. Hazardous to the aquatic environment — Chronic category 3.

Human health hazards : Causes skin irritation. May cause drowsiness or dizziness. Exposure to high vapour concentrations

may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately

concentrating and inhaling contents can be harmful or fatal.

Physical/chemical hazards : Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a

naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures

exceeding 50 °C.

Environmental hazards : Harmful to aquatic life with long lasting effects.

Other information : Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short

period only. Ventilate well after use. Harmful to house pets.

2.2. Label elements

Label elements ((EU) 1272/2008):

Hazard pictograms



Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

Product name : Shell Rust Remover Page 1/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms



Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: Contains: Kerosine (petroleum), hydrodesulfurized .

2.3. Other hazards

Other information

: The classification of this product is based on the non-aerosolised form of the mixture (on basis of section 1.1.3.7. of Regulation (EC) No 1272/2008). Does not contain PBT or vPvB substances. Human health: This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605. Environment: This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Product name : Shell Rust Remover Page 2/12

Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemety

Substance name	Concentration	CAS nr.	EC number	Remark	REACH nr.
	(w/w) (%)				
Hydrocarbons, C10-C13, n-alkanes,	10 - < 25		918-481-9		01-2119457273-39
isoalkanes, cyclics, < 2% aromatics					
Butane	10 - < 25	106-97-8	203-448-7		01-2119474691-32
Distillates (petroleum), hydrotreated	10 - < 25	64742-53-6	265-156-6		01-2119480375-34
light naphthenic					
Kerosine (petroleum), hydrodesulfur-	10 - < 25	64742-81-0	265-184-9		01-2119462828-25
ized					
Propane	10 - < 25	74-98-6	200-827-9		01-2119486944-21
Distillates (petroleum), hydrotreated	2,5 - < 10	64742-55-8	265-158-7		01-2119487077-29
light paraffinic					
Isobutane	2,5 - < 10	75-28-5	200-857-2		01-2119485395-27
Lubricating oils (petroleum), C20-50,	2,5 - < 10	72623-87-1	276-738-4		01-2119474889-13
hydrotreated neutral oil-based					
Hydrocarbons, C12-C15, n-alkanes,	1 - < 2,5		920-107-4		01-2119453414-43
isoalkanes, cyclics, < 2% aromatics					
Lubricating oils (petroleum), C15-30,	1 - < 2,5	72623-86-0	276-737-9		01-2119474878-16
hydrotreated neutral oil-based					

Substance name	Hazard Class	H-phrases	Pictograms
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Asp. Tox. 1	H304; EUH066	GHS08
Butane	Flam. Gas 1A; Press. Gas	H220; H280	GHS02; GHS04
Distillates (petroleum), hydrotreated light naphthenic	Asp. Tox. 1	H304	GHS08
Kerosine (petroleum), hydrodesulfur- ized	Flam. Liq. 3; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aquatic Chronic 2		GHS02; GHS07; GHS08; GHS09
Propane	Flam. Gas 1A; Press. Gas	H220; H280	GHS02; GHS04
Distillates (petroleum), hydrotreated light paraffinic	Asp. Tox. 1	H304	GHS08
Isobutane	Flam. Gas 1A; Press. Gas	H220; H280	GHS02; GHS04
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Asp. Tox. 1	H304	GHS08
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Asp. Tox. 1	H304; EUH066	GHS08
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Asp. Tox. 1	H304	GHS08

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries

up. Consult a doctor if irritation persists.

Product name : Shell Rust Remover Page 3/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemetyl

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.

Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to

respiratory airways and coughing.

Skin contact : Irritant. May cause redness. Repeated exposure may cause skin dryness or cracking.

Eye contact : May cause stinging of eyes and redness.
Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog. Not suitable : Water jet. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50

°C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to

cool container and prevent explosion of the aerosol.

Hazardous thermal decomposition and combustion products

: Carbon monoxide may be evolved if incomplete combustion occurs.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

: Fight a fire where aerosols are involved from a protected position. Use adequate respiratory

equipment in case of insufficient ventilation.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact

with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours

are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. Waste product should not

be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Collect aerosol cans in an approved container. Do not pierce

aerosols. Wash away remainder with plenty of water and soap.

Product name : Shell Rust Remover Page 4/12

Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

6.4. Reference to other sections

Reference to other sections: See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated

areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep away from oxidizing agents. Keep frost-free, in a cool (< 35°), dry and well-ventilated place.

Protect from sunlight and keep away from heat.

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have

not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Hydrocarbons, C10-C13, n-alkanes,		1200	-	 -	CEFIC-HSPA
isoalkanes, cyclics, < 2% aromatics					
Butane	GB	1450	1810	-	
		1450	1810		MAC: UK
Kerosine (petroleum),		350	-	CEFIC-HSPA	
hydrodesulfurized					
Propane		1800	-		MAC: BG, PL, CH, SL,
					etc
Isobutane		1900	2400		MAC: FI, BE, CH
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics		1200	}	-	Supplier information

Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
Distillates (petroleum), hydrotreated light naphthenic	Inhalation			5,6 mg/m3	2,7 mg/m3
	Dermal				1 mg/kg bw/day

Product name : Shell Rust Remover Page 5/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemety

Lubricating oils (petroleum), C20-50,	Inhalation		5.58 mg/m3	2.73 mg/m3
hydrotreated neutral oil-based				
	Dermal			0.97 mg/kg bw/day
Lubricating oils (petroleum), C15-30,	Inhalation		5,58 mg/m3	2,73 mg/m3
hydrotreated neutral oil-based				
	Dermal			0,97 mg/kg bw/day

Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
Distillates (petroleum), hydrotreated	Oral				0,74 mg/kg bw/day
light naphthenic					
Lubricating oils (petroleum), C20-50,	Oral				0.74 mg/kg bw/day
hydrotreated neutral oil-based					
Lubricating oils (petroleum), C15-30,	Oral				0,74 mg/kg bw/day
hydrotreated neutral oil-based					

Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
Distillates (petroleum), hydrotreated	Oral			9,33 mg/kg food
light naphthenic				
Distillates (petroleum), hydrotreated	Oral			9,33 mg/kg food
light paraffinic				
Lubricating oils (petroleum), C20-50,	Oral			9.33 mg/kg food
hydrotreated neutral oil-based				
Lubricating oils (petroleum), C15-30,	Oral			9.33 mg/kg food
hydrotreated neutral oil-based				

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.



Body protection : Use of specific protective industrial clothing is not required for momentary use. Wear suitable

protective clothing, overalls or suit, and similar boots in accordance with EN 365/367 resp. 345 in case of frequent or prolonged use and in case of large scale exposure. Suitable material: nitril.

Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

with EN 140.

Hand protection : Wear appropriate safety gloves in accordance with EN 374. Suitable material: nitril. ± 0,5 mm.

Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Product name : Shell Rust Remover Page 6/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemetyl

9.1. Information on basic physical and chemical properties

Physical state : Aerosol.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not known.

pH : Not applicable. Waterfree product.

Not known.

Solubility in water : Active ingredients not soluble. Propellant(s) not soluble.

Partition coefficient (n-oc-

tanol/water)

Flash point

Not applicable. Not measurable.

Flammability (solid, gas) : Extremely flammable. Ignition distance and time equivalent needed to achieve ignition: Not

measured.

Not measured. Not relevant for mixtures.

Pressurised container: May burst if heated.

Auto ignition temperature : Not applicable. Aerosol container explodes before reaching the auto-ignition point.

Not measurable.

Boiling point/boiling range : Not known.

Melting point/melting range : < -20 °C

Explosive properties

Explosion limits (% in air) : 0,6 - 10,9

Oxidising properties : Not applicable. Does not contain oxidizing substances.

Decomposition temperature: Not applicable. Aerosol explodes before reaching the decomposition temperature.

Viscosity (20°C) : Not known. Not measurable. Viscosity (40°C) : Not known. Not measurable.

Vapour pressure (20°C) : 400000 Pa

Relative vapour density : Not known (air = 1)

Relative density (20°C) : 0,707 g/ml

Particle characteristics : Not applicable. Liquid.

9.2. Other information

Other information : Not relevant.

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

10.5. Incompatible materials

Materials to avoid : Not applicable.

10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

Product name : Shell Rust Remover : Page 7/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

SECTION 11 TOXICOLOGICAL INFORMATION

*

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.

Inhalation

Acute toxicity : Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: < 1 %. ATE: > 5 mg/l. Low toxicity. Not

classified - based on available data, the classification criteria are not met. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness

and death.

Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data,

the classification criteria are not met.

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Skin contact

Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 5000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Irritant. May cause redness. Prolonged contact may dry out and defat the skin.

Sensitisation : Does not contain skin sensitisers. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Eve contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not

met.

Ingestion

Acute toxicity : Aerosol or mist: Ingestion is unlikely to occur. Calculated LD50: > 1231 mg/kg.bw. Ingredients of

unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available

data, the classification criteria are not met.

Aspiration : Aerosol or mist: Ingestion is unlikely to occur. Not classified - based on available data, the

classification criteria are not met.

Corrosion/irritation : Aerosol or mist: Ingestion is unlikely to occur. May cause a feeling of sickness, stomachache,

vomiting and diarrhoea.

Carcinogenicity : Aerosol or mist: Ingestion is unlikely to occur. Not expected to be carcinogenic. Not classified -

based on available data, the classification criteria are not met.

Mutagenicity : Aerosol or mist: Ingestion is unlikely to occur. Does not contain mutagenic substances. Not

classified - based on available data, the classification criteria are not met.

Reprotoxicity : Aerosol or mist: Ingestion is unlikely to occur. Development: Not expected to be reprotoxic.

Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the

classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
Kerosine (petroleum), hydrodesulfurized	Skin sensitisation	Not sensitizing		Guinea pig
	LD50 (oral) - estimate	> 5000 mg/kg bw	Read across	Rat

Product name : Shell Rust Remover Page 8/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemetyl

LC50 (inhalation) -	> 5000 mg/m3	Read across	Rat
estimate			
LD50 (dermal) -	> 2000 mg/kg bw	Read across	Rabbit
estimate			
NOAEL (oral) -	750 mg/kg bw/d	Read across	Rabbit
estimate			
NOAEL (inhalation) -	> 1000 mg/m3	Read across	Mouse
estimate			
Skin irritation - estimate	Irritant	Read across	Rabbit
Eye irritation - estimate	Slightly irritant	Read across	Rabbit
NOAEL (development)	1000 mg/kg.d	Read across	Rat
- estimate			
Skin sensitisation -	Not sensitizing	Read across	Guinea pig
estimate			-

11.2. Information on other hazards

Endocrine disrupting

properties Other information : This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

: Not applicable.

SECTION 12 **ECOLOGICAL INFORMATION**

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity

: Harmful to aquatic organisms. Calculated LC50 (fish): 11 mg/l. Calculated EC50 (waterflea): 7 mg/l.

Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence - degradability: May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility : Not applicable.

12.5. Results of PBT and vPvB assessment

: Does not contain PBT or vPvB substances. PBT/vPvB assessment

12.6. Endocrine disrupting properties

Endocrine disrupting properties

: This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

12.7. Other adverse effects

Other adverse effects : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Kerosine (petroleum), hydrodesulfurized	NOEC (fish)	1 mg/l.d		
1 3	EC50 (waterflea)	1,4 mg/l	OECD 202	Daphnia magna

Product name : Shell Rust Remover Page 9/12 Revision : 2024-03-14 Replaces issue dated : 2022-04-06 **INFO CARE SDS**



According to Regulation (EU) No 2020/878

Kemetyl

<u> </u>	ICEO (algoa)	> 1 mg/l	OECD 201	Pseudokirchnerella
	IC50 (algea)	> 1 111g/1		subcapitata
	NOEC (waterflea) - chronic	0,48 mg/l.d	OECD 211	Daphnia magna
l .	NOEC (fish) - estimate	0,098 mg/l.d		
	Ultimate aerobic	58,6 %	OECD 301 F	
	biodegradation (%)			
	LC50 (fish) - estimate	> 2 mg/l	OECD 203	Oncorhynchus mykiss

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack

with waste produced by households. Containers may be recycled. Treat product residues and non-

empty pack as hazardous waste.

Additional warning : Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be

complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number

UN nr. : UN 1950 . For IATA only: ID 8000

14.2. UN proper shipping name

Transport name : AEROSOLS . For IATA only: CONSUMER COMMODITY Transport name (IMDG, : AEROSOLS . For IATA only: CONSUMER COMMODITY

IATA)

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : 2
Classification code : 5F
Packaging group : Danger label : 2,1
Tunnel restriction : D

code



Other information : Not intended for carriage by tank-vessels on inland waterways.

IMDG (sea)

Class : 2,1 Packaging group : -

EmS (fire / spill) : F - D / S - U

Product name : Shell Rust Remover Page 10/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemetyl

Marine pollutant : No

IATA (air)

Class : 2,1 ERG code : 9L

14.6. Special precautions for user

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies

to the transport of this product. An IATA ID8000 Consumer Commodity package must bear an Air

Limited Quantity marking and a Class 9 hazard label.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2020/878 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC

(aerosols) and other regulations. Directive 2008/98/EC (waste).

: This product is exempted from classification as "May be fatal if swallowed and enters airways" on

basis of section 3.10.1.6.3. of Annex I of Regulation (EC) No 1272/2008.

: In the UK it is recommended that all aerosols should be labelled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill

Instantly' accompanied by the phrase 'Use only as directed'.

15.2. Chemical safety assessment

Chemical safety assessment

: Not applicable.

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2020/878 dated 18 June 2020 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be used (but not necessarily are used) in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association

Product name : Shell Rust Remover Page 11/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Kemetyl

IBC code : The IMO International Code for construction and equipment of ships carrying dangerous chemicals

in bulk.

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MAC : Maximum Allowable Concentration

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development

PBT : Persistent, Bioaccumulative and Toxic

PC : Chemical product category

PT : Product type

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

SU : Sector of Use

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

UFI : Unique formula identifier
VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Flam. Aer. 1 : Expert judgement.
Skin Irrit. 2 : Calculation method.
STOT SE 3 : Calculation method.
Aquatic Chronic 3 : Calculation method.

Full text of hazard classes mentioned in section 3:

Flam. Gas 1 : Flammable gas, category 1.
Flam. Liq. 3 : Flammable liquid, category 3.
Skin Irrit. 2 : Skin irritation, category 2.
Press. Gas : Gases under pressure.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

Asp. Tox. 1 : Aspiration hazard, category 1.

Aquatic Chronic 2 : Hazardous to the aquatic environment — Chronic category 2.

Full text of H-phrases mentioned in section 3:

H220 Extremely flammable gas. H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Advice on any training appropriate for workers: none.

Country / Language code : EC / EN

Number format : "," used as decimal separator.

End of safety data sheet.

Print date : 2024-03-18

Product name : Shell Rust Remover Page 12/12
Revision : 2024-03-14 Replaces issue dated : 2022-04-06 INFO CARE SDS