

According to Regulation (EU) No 2020/878

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SHELL START GAS

Product code : U1472, AT08S; AT07S; 30431; 09727038

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC0 Other. Other products for chemical or technical processes.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Polska Sp. z o. o.

Al. Jerozolimskie 146 02-305 Warszawa, Poland

 Telephone
 : +48 22 822 5390

 E-mail
 : msds@kemetyl.com

 Website
 : www.kemetyl.pl

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

PL - Telephone : +48 22 822 5390 (During office hours only)

### SECTION 2 HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

CLP classification : Aerosols, cate

(1272/2008/EC)

: Aerosols, category 1. Skin irritation, category 2. Aspiration hazard, category 1. Specific target organ toxicity after single exposure, category 3. Hazardous to the aquatic environment — Chronic

category 3.

Human health hazards

: May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Exposure to high vapour concentrations may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or

fatal.

Physical/chemical hazards :

Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures

exceeding 50 °C.

Environmental hazards

: Harmful to aquatic life with long lasting effects.

Other information

: Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short period only. Ventilate well after use. Harmful to house pets.

### 2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms :







Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

Product name : Shell Start Gas Page 1/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms :







Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: Contains: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics .

### 2.3. Other hazards

Other information : The classification of this product is based on the non-aerosolised form of the mixture (on basis of

section 1.1.3.7. of Regulation (EC) No 1272/2008). Does not contain PBT or vPvB substances in

concentrations higher than 0,1%.

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## 3.2. Mixtures

Product name : Shell Start Gas Page 2/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

# Kemetyl

Product description : Mixture.

Information on hazardous substances:

mornation on nazaraode odoctanood.					
Substance name	Concentration (w/w) (%)	CAS nr.	EC number	Remark	REACH nr.
Butane	20 - 30	106-97-8	203-448-7		
Dimethoxymethane	20 - 30	109-87-5	203-714-2		01-2119664781-31
Hydrocarbons, C7-C9, n-alkanes,	10 - 20		920-750-0		01-2119473851-33
isoalkanes, cyclics					
Propane	10 - 20	74-98-6	200-827-9		
Tert-butyl methyl ether	1 - 10	1634-04-4	216-653-1		01-2119452786-27
Isobutane	1 - 10	75-28-5	200-857-2		

Substance name	Hazard Class	H-phrases	Pictograms
Butane	Flam. Gas 1A; Press.	H220; H280	GHS02; GHS04
	Gas		
Dimethoxymethane	Flam. Liq. 2	H225	GHS02
Hydrocarbons, C7-C9, n-alkanes,	Flam. Liq. 2; Asp. Tox.	H225; H304; H336;	GHS02; GHS07;
isoalkanes, cyclics	1; STOT SE 3; Aquatic	H411; EUH066	GHS08; GHS09
	Chronic 2		
Propane	Flam. Gas 1A; Press.	H220; H280	GHS02; GHS04
	Gas		
Tert-butyl methyl ether	Flam. Liq. 2; Skin Irrit. 2	H225; H315	GHS02; GHS07
Isobutane	Flam. Gas 1A; Press.	H220; H280	GHS02; GHS04
	Gas		

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

# SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries

up. Consult a doctor if irritation persists.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.

Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to

respiratory airways and coughing.

Skin contact : Irritant. May cause redness. Repeated exposure may cause skin dryness or cracking.

Eye contact : May cause stinging of eyes and redness.

Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause lung damage, sore throat and

lack of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

Product name : Shell Start Gas Page 3/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

#### 5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog. Not suitable : Water jet. Use of heavy stream of water may spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50

°C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to

cool container and prevent explosion of the aerosol.

Hazardous thermal decomposition products : Carbon monoxide may be evolved if incomplete combustion occurs.

#### 5.3. Advice for firefighters

Special protective equipment for fire-fighters : Fight a fire where aerosols are involved from a protected position. Use adequate respiratory

equipment in case of insufficient ventilation.

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact

with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours

are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

# 6.2. Environmental precautions

Environmental precautions: Avoid release of product into sewers, surface water and/or ground water. Waste product should not

be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

# 6.3. Methods and material for containment and cleaning up

: Collect spilled material in containers. Collect aerosol cans in an approved container. Do not pierce Methods for cleaning up

aerosols. Wash away remainder with plenty of water and soap.

### 6.4. Reference to other sections

Reference to other sections: See also section 8.

#### **HANDLING AND STORAGE SECTION 7**

### 7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated

> areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

#### 7.2. Conditions for safe storage, including any incompatibilities

Product name : Shell Start Gas Page 4/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

Storage : Keep away from oxidizing agents. Keep frost-free, in a cool (< 35°), dry and well-ventilated

place. Protect from sunlight and keep away from heat. Keep away from food, drink and animal

feedingstuffs.

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

\*

### 8.1. Control parameters

Occupational exposure limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have

not been established for this product.

### Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Butane	GB	1450	1810	-	
		1450	1810	İ	MAC: UK
Dimethoxymethane	GB	3160	3950	-	
		3100			MAC: various EU Member States
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		1200	}	CEFIC-HSPA	
Propane		1800	}		MAC: BG, PL, CH, SL, etc
Tert-butyl methyl ether	EC	183,5	367	-	Directive 2009/161/EU
	GB	183,5	367	-	
Isobutane		1900	2400		MAC: FI, BE, CH

# Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-term D		DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
Dimethoxymethane Hydrocarbons, C7-C9, n-alkanes,	Dermal Inhalation Inhalation				17,9 mg/kg bw/day 126,6 mg/m3 2035 mg/m3
isoalkanes, cyclics	Dermal				773 mg/kg bw/day
Tert-butyl methyl ether	Inhalation Dermal	357 mg/m3			178,5 mg/m3 5100 mg/kg bw/day

# Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-t	DNEL, short-term		DNEL, long-term	
	exposure					
	,	Local effect	Systemic effect	Local effect	Systemic effect	
Dimethoxymethane  Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Dermal Inhalation Oral Inhalation				18,1 mg/kg bw/day 31,5 mg/m3 18,1 mg/kg bw/day 608 mg/m3	
, , , , , , , , , , , , , , , , , , , ,	Dermal Oral				699 mg/kg bw/day 699 mg/kg bw/day	

Product name : Shell Start Gas Page 5/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

# Kemetyl

Tert-butyl methyl ether	Inhalation	214 mg/m3		53,6 mg/m3
	Dermal			3570 mg/kg bw/day
	Oral			7,1 mg/kg bw/day

### Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
Dimethoxymethane	Water	14,577 mg/l	1,477 mg/l	
	Sediment	13,135 mg/kg	1,3135 mg/kg	
	STP			10 mg/l
	Soil			4,6538 mg/kg
Tert-butyl methyl ether	Water	5,1 mg/l	0,26 mg/l	
	Sediment	23 mg/kg	1,17 mg/kg	
	Intermittent water			47,2 mg/l
	STP			71 mg/l
	Soil			1,56 mg/kg

### 8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

In S

Body protection : Use of specific protective industrial clothing is not required for momentary use. Wear suitable

protective clothing, overalls or suit, and similar boots in accordance with EN 365/367 resp. 345 in case of frequent or prolonged use and in case of large scale exposure. Suitable material: butyl.

Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

Not measured. Not relevant for mixtures.

with EN 140.

Hand protection : Wear appropriate safety gloves in accordance with EN 374. Suitable material: butyl. ± 0,5 mm.

Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state : Aerosol.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not known.

pH : Not applicable. Waterfree product.
Solubility in water : Active ingredients not soluble. Propellant(s) not soluble.

Solubility in water : Partition coefficient (n-oc- : Not known.

tanol/water)

Flash point : Not applicable. Not measurable.

Flammability (solid, gas) : Extremely flammable. Contains  $\geq$  85% flammable components and has a heat of combustion  $\geq$ 

30 kJ/g.

Product name : Shell Start Gas Page 6/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

Auto ignition temperature Boiling point/boiling range : Not applicable. Not known.

Aerosol container explodes before reaching the auto-ignition point.

Not measurable.

Melting point/melting range:

< -20 °C

Explosive properties

0.9 - 17.6

Explosion limits (% in air) Oxidising properties

Not applicable. Not applicable. Does not contain oxidizing substances.

Pressurised container: May burst if heated.

Decomposition temperature: Viscosity (20°C)

Not known.

Aerosol explodes before reaching the decomposition temperature. Not measurable.

Viscosity (40°C)

Not known. 350000 Pa

Not measurable.

Vapour pressure (20°C) Relative vapour density

: > 1

(air = 1)

Relative density (20°C)

: 0,65 g/ml

Particle characteristics : Not applicable.

Liquid.

9.2. Other information

Other information : Not relevant.

#### **SECTION 10** STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity : See sub-sections below.

### 10.2. Chemical stability

Stability : Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

#### 10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

# 10.5. Incompatible materials

Materials to avoid : Not applicable.

#### 10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product. Inhalation

: Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: < 1 %. ATE: > 5 mg/l. Low toxicity. Not Acute toxicity

> classified - based on available data, the classification criteria are not met. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness

and death.

Product name : Shell Start Gas Page 7/12 Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data,

the classification criteria are not met.

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria

are not met.

Skin contact

Acute toxicity : Calculated LD50: > 3452 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Irritant. May cause redness. Prolonged contact may dry out and defat the skin. Sensitisation : Not classified - based on available data, the classification criteria are not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria

are not met.

Eye contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not

met.

Ingestion

Acute toxicity : Aerosol or mist: Ingestion is unlikely to occur. Calculated LD50: > 1400 mg/kg.bw. Ingredients of

unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available

data, the classification criteria are not met.

Aspiration : Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can

be fatal. If swallowed, if any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 38.3° C, shortness of breath,

chest congestion or continued coughing or wheezing.

Corrosion/irritation : Aerosol or mist: Ingestion is unlikely to occur. May cause a feeling of sickness, stomachache,

vomiting and diarrhoea.

Carcinogenicity : Aerosol or mist: Ingestion is unlikely to occur. Not expected to be carcinogenic. Not classified -

based on available data, the classification criteria are not met.

Mutagenicity : Aerosol or mist: Ingestion is unlikely to occur. Not expected to be mutagenic. Not classified - based

on available data, the classification criteria are not met.

Reprotoxicity : Aerosol or mist: Ingestion is unlikely to occur. Development: Not expected to be reprotoxic.

Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the

classification criteria are not met.

### Toxicological information:

Chemical name	Property		Method	Test animal
Hydrocarbons, C7-C9, n-alkanes,	LD50 (dermal)	> 2920 mg/kg bw	OECD 402	Rat
isoalkanes, cyclics				
	LC50 (inhalation)	> 23300 mg/m3	OECD 403	Rat
	LD50 (oral)	> 5840 mg/kg bw	OECD 401	Rat
	Eye irritation	Non-irritant		
	Skin irritation	Non-irritant		
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	Genotoxicity - in vivo	Not genotoxic	OECD 474	Mouse
	Genotoxicity - in vitro	Not genotoxic	OECD 473	
	NOAEL (development)	Not teratogenic	Read across	
	- estimate			
	NOAEL (inhalation)	5800 mg/m3	OECD 413	Rat
	NOAEL (fertility) -	Not reprotoxic	Read across	
	estimate			
	Inhalation sensitisation	Not sensitizing		ļ

Product name : Shell Start Gas Page 8/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

	Skin sensitisation	Not sensitizing		
	NOEL (carcinogenicity)	Not carcinogenic		
	- estimate			
Tert-butyl methyl ether	NOAEL (inhalation)	2880 mg/m3		Rat
	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig
	LD50 (oral)	> 2000 mg/kg bw	OECD 401	Rat
	LD50 (dermal)	> 2000 mg/kg bw	OECD 402	Rat
	Skin irritation	Moderately irritant	OECD 404	Rabbit
	Eye irritation	Slightly irritant	OECD 405	Rabbit
	NOAEL (oral)	300 mg/kg bw/d	OECD 408	Rat
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	Genotoxicity - in vitro	Not genotoxic	OECD 476	Chinese Hamster
	Genotoxicity - estimate	Not genotoxic		Rat
	NOAEL (fertility, inh.)	Not reprotoxic		Rat
	NOAEL (developmental	Not teratogenic		Rat
	toxicity, inh.)			

#### 11.2. Information on other hazards

**Endocrine disrupting** 

Other information

properties

#### **SECTION 12 ECOLOGICAL INFORMATION**

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

: Not applicable.

: Not applicable.

**Ecotoxicity** : Harmful to aquatic organisms. Calculated LC50 (fish): 17 mg/l. Calculated EC50 (waterflea): 26 mg/

I. Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence - degradability: May cause long-term adverse effects in the aquatic environment. The surfactants contained in

this preparation do not comply with the biodegradability criteria as laid down in Regulation (EC)

648/2004 on detergents. This product shall not be used in cleaners.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.5. Results of PBT and vPvB assessment

: Does not contain PBT or vPvB substances in concentrations higher than 0,1%. PBT/vPvB assessment

12.6. Endocrine disrupting properties

**Endocrine disrupting** 

: Not applicable.

properties

12.7. Other adverse effects

Other adverse effects : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Hydrocarbons, C7-C9, n-alkanes,	EC50 (waterflea)	4,6 mg/l	OECD 202	Daphnia magna
isoalkanes, cyclics				

Product name : Shell Start Gas Page 9/12 Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

# Kemetyl

IC50 (algea)	10 mg/l		Pseudokirchnerella subcapitata
LC50 (fish)	> 3 mg/l	OECD 203	Oncorhynchus mykiss
NOEC (waterflea) - chronic	1 mg/l.d	OECD 211	Daphnia magna
NOEC (fish)	0,574 mg/l.d		Oncorhynchus mykiss
Ultimate aerobic	> 60 %	Read across	
biodegradation (%)			
Log P(ow)	4,85		

### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack

with waste produced by households. Containers may be recycled. Treat product residues and non-

empty pack as hazardous waste.

Additional warning : Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be

complied with.

### SECTION 14 TRANSPORT INFORMATION

#### 14.1. UN number or ID number

UN nr. : UN 1950 . For IATA only: ID 8000

### 14.2. UN proper shipping name

Transport name : AEROSOLS . For IATA only: CONSUMER COMMODITY Transport name (IMDG, : AEROSOLS . For IATA only: CONSUMER COMMODITY

IATA)

# 14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : 2
Classification code : 5F
Packaging group : Danger label : 2,1
Tunnel restriction : D

code



Other information : Not intended for carriage by tank-vessels on inland waterways.

IMDG (sea)

Class : 2,1 Packaging group : -

Product name : Shell Start Gas Page 10/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

# Kemetyl

EmS (fire / spill) : F - D / S - U

Marine pollutant : No

IATA (air)

Class : 2,1 ERG code : 9L Packaging group : -

### 14.6. Special precautions for user

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies

to the transport of this product. An IATA ID8000 Consumer Commodity package must bear an Air

Limited Quantity marking and a Class 9 hazard label.

### 14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

#### SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2020/878 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC

(aerosols) and other regulations. Directive 2008/98/EC (waste).

: In the UK it is recommended that all aerosols should be labelled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill

Instantly' accompanied by the phrase 'Use only as directed'.

### 15.2. Chemical safety assessment

Chemical safety assessment

: Not applicable.

## **SECTION 16 OTHER INFORMATION**

## 16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2020/878 dated 18 June 2020 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association
IBC code : International Bulk Chemical Code

Product name : Shell Start Gas Page 11/12

Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 INFO CARE SDS



According to Regulation (EU) No 2020/878

# Kemetyl

**IMDG** International Maritime Dangerous Goods Code LD50/LC50 Lethal Dose/Concentration for 50% of a population

Maximum Allowable Concentration MAC

International Convention for the Prevention of Pollution From Ships MARPOL

NO(A)EL No Observed (Adverse) Effect Level

OECD Organisation for Economic Co-operation and Development

**PBT** Persistent, Bioaccumulative and Toxic

PC Chemical product category

PT Product type

**REACH** Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulations concerning the International Carriage of Dangerous Goods by Rail RID

Sewage Treatment Plant STP

Sector of Use SU

Time-Weighted Average/Short Term Exposure Limit TWA/STEL

UN **United Nations** 

UFI Unique formula identifier VOC Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Flam. Aer. 1 : Expert judgement. Skin Irrit. 2 : Calculation method. STOT SE 3 : Calculation method. Asp. Tox. 1 : Expert judgement. Aquatic Chronic 3 : Calculation method.

Full text of hazard classes mentioned in section 3:

Flam. Gas 1 : Flammable gas, category 1. Flam. Liq. 2 : Flammable liquid, category 2. Skin Irrit. 2 : Skin irritation, category 2.

Skin Sens. 1/1A/1B : Skin sensitization, category 1/1A/1B.

Press. Gas : Gases under pressure.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

: Aspiration hazard, category 1. Asp. Tox. 1

: Hazardous to the aquatic environment — Chronic category 2. Aquatic Chronic 2

Full text of H-phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H411

Toxic to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking. **EUH066** 

Advice on any training appropriate for workers: none.

Number format : "," used as decimal separator.

End of safety data sheet.

Print date : 2023-05-22

Product name : Shell Start Gas Page 12/12 Date of issue : 2022-07-06 Replaces issue dated : 2018-12-27 **INFO CARE SDS**