

# Technical Data Sheet (TDS)

## Shell Contact Spray



Shell Contact Spray removes and cleans dirt, grease, sulphides and oxides. It removes high contact resistance and maintains the electrical conductivity of parts to working level.

### Performance Features and Benefits

- Ignition coils, distributor head, spark plug cables and spark plug caps are the main areas.
- Prevents failures due to humidity in electrical installations.
- It improves electrical conductivity, reduces friction and wear.
- It provides resistance against external influences such as humidity, rust and corrosion.

### Typical Properties\* ;

Density	ASTM 4052	0,65
pH, @20°C	ASTM D-1287	8,26
Color		Transparent yellow

**\* All figures are typical values and do not constitute a specification.**

*The content of this Technical Data Sheet has been prepared by taking into consideration the relevant international standards and the information contained in specifications of vehicle and equipment manufacturers. This Technical Data Sheet and the statements in content cannot be interpreted as a guarantee commitment in respect of product specifications or usage in any application.*

*It is the consumer's responsibility to use this product in accordance with its ordinary purpose and comply with the applicable laws and regulations. Kemetyl Kimya San. Tic. Ltd. Şti. shall not be held responsible for any claims or damages arising out of abnormal use, improper usage, use for the wrongful purposes or risks and consequences by the nature of product structure.*

*This Technical Data Sheet shall be valid on issue date. Right to amend information provided in content of this Technical Data Sheet without prior notice is reserved.*